



(NOTE) 1. OPERATING PRESS. FOR CYLINDER: 0.34~0.59MPa  
 2. DIRECTION OF INLET FOR OPERATING PRESSURE IS VARIABLE AT USER'S REQUEST.  
 3. TEMPERATURE RANGE : -10 ~ 80°C  
 4. CV VALUE : 2.8  
 5. MATERIALS OF WETTED PORTION IN REPLACE UPPER ASSEMBLY.

| NAME OF PARTS  | MATERIAL |
|----------------|----------|
| STEM           | SUS 316L |
| BELLOWS        | SUS 316L |
| BELLOWS FLANGE | SUS 316L |
| DISK PACKING   | PCIFE    |
| GASKET         | PCIFE    |

LENGTH OF EFFECTIVE THREAD: 8

| REV. MARK | DATE | CONTENTS | REVISED |
|-----------|------|----------|---------|
| △         |      |          | 承認      |
| △         |      |          | 承認      |
| △         |      |          | 承認      |

|                 |        |
|-----------------|--------|
| STANDARD        | UP     |
| CODE No. 413975 | 413976 |

| DATE       | MPa  | HYDRO     | GR% |
|------------|------|-----------|-----|
| 2003-12-19 |      | 水圧        | 1.5 |
| SCALE      | FREE | SEAL      | 1.1 |
| APPR.      |      | SEAT      | 1.1 |
| CHECKED    |      | BACK SEAT | 1.1 |
| DESIGN     |      | SEAL      | 1.1 |

| DATE       | MPa  | HYDRO     | GR% |
|------------|------|-----------|-----|
| 2003-12-19 |      | 水圧        | 1.5 |
| SCALE      | FREE | SEAL      | 1.1 |
| APPR.      |      | SEAT      | 1.1 |
| CHECKED    |      | BACK SEAT | 1.1 |
| DESIGN     |      | SEAL      | 1.1 |

| REV. MARK | DATE | CONTENTS | REVISED |
|-----------|------|----------|---------|
| △         |      |          | 承認      |
| △         |      |          | 承認      |
| △         |      |          | 承認      |

|             |   |
|-------------|---|
| ITEM NO.    | FPR-71-19.05-AVU                          |
| NAME        | STAINLESS STEEL IMP - #19.05              |
| DESCRIPTION | UJR TYPE AIR OPERATED BELLOW VALVE (N.C.) |
| DRG. NO.    | KU150735E                                 |
| REV. MARK   | 承認  |

|           |      |      |      |      |      |       |       |      |       |      |       |       |       |       |       |       |       |       |
|-----------|------|------|------|------|------|-------|-------|------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 呼称 (A呼称)  | 6    | 8    | 10   | 15   | 20   | 25    | 32    | 40   | 50    | 65   | 80    | 100   | 125   | 150   | 200   | 250   | 300   |       |
| 呼称 (B呼称)  | 1/4  | 3/8  | 1/2  | 3/4  | 1    | 1 1/4 | 1 1/2 | 2    | 2 1/2 | 3    | 3 1/2 | 4     | 5     | 6     | 7     | 8     | 9     | 10    |
| 標準寸法 (mm) | 10.5 | 13.8 | 17.3 | 22.2 | 28.0 | 34.0  | 42.7  | 48.5 | 60.5  | 76.3 | 98.1  | 125.0 | 157.5 | 200.0 | 254.0 | 315.0 | 381.0 | 450.0 |