



3.2 SIZE

DIA	MAX PRESSURE (MPa)	TEMPERATURE (°C)	MAX CV
3.2	4.90	-10 ~ 80	0.05
6.35	4.90	-10 ~ 80	0.3
9.52	4.90	-10 ~ 80	1.0
12.7	4.90	-10 ~ 80	1.37

REVISION				
REV. MARK	DATE	CONTENTS	REVISED	APPD.
改訂	日付	改訂内容	改訂	承認
△	94-10-03	Rev	R.M	RS
△	00-05-26	Changed to a unit of SI		
△	01-09-25	Revision of size of of 2.6.35, φ9.52		
△	06-05-30	Addition φ3.2		

REMARK  
備考

ITEM NO.	PART NAME	MATERIAL	QTY	REMARK	G.T.No.
18	DISK HOLDER	SUS 316	1		
17	NUT	SUS 316	2	AP PLATING	
16	BACK RING	SUS 316	2		
15	FRONT RING	SUS 316	2		
14	NAME PLATE	PTIC	1	BLUE	
13	SET SCREW	SUS 304	1		
12	HAND WHEEL	A5050	1	ALUMITE	
11	SHEET PACKING	PCTFE	1		
10	PANEL NUT	SUS 304	1		
9	RING	SUS 316	1		
8	GLAND PACKING	PTFE+PEA	1set		
7	GLAND NUT	SUS 304	1		
6	GLAND	SUS 316	1		
5	DISK	PCTFE	1		
4	STEM	SUS 316	1		
3	BONNET NUT	SUS 304	1		
2	BONNET	SUS 316	1		
1	BODY	SUS 316L	1		

CODE No.	STANDARD
FUD-95-3.2	100449
FUD-95-6.35	100450
FUD-95-9.52	100451
FUD-95-12.7	100452

MATERIAL LIST				
DATE	SCALE	MPa	HYDRO	GHe
日付	尺度	耐圧	水压	気圧
84.5.19	FREE	5.39	7.35	5.39

DIA	d1	L1	L2	L3	B1	h	d2	(H)	l	D	B2	R1	A	C	d3	ITEM. NO
3.2	2.5	57	44	13	10	24	14.5	69	7	32	21	10	15	12	M5	FUD-95-3.2
6.35	5	63	49	15	14	24	16.5	73	7	40	21	9.5	15	12	M5	FUD-95-6.35
9.52	8	71	55	17.5	17	26	20.5	81	7	50	26	11.5	20	15	M5	FUD-95-9.52
12.7	8	81	59	24	22	27	20.5	82	7	50	26	14	20	15	M5	FUD-95-12.7

ORD. NO.	ITEM NO.	RECIPIENT	NAME	DRG. NO.	REV. MARK
製番	品番	納入先	名称	図番	改訂
			F900 TYPE DISK VALVES	U12094	4
			PRESSURE RATING 4.90 MPa		

Fujikin International, Inc.  
株式会社 フジキン

CAREER	呼び番号	呼び径(A呼称)	呼び径(B呼称)	鋼管外径 (mm)
来歴	対比表	6	8	10
		1/4	3/8	1/2
		3/4	1	1 1/4
		1 1/2	2	2 1/2
		3	3 1/2	4
		5	6	8
		10	15	20
		25	32	40
		50	65	80
		90	100	125
		150	200	250
		300	350	400

UNIT [mm] THE THIRD ANGLE 第三角法

TYPE 型式 CAB. NO.